

Driver Name : _____
 Firmware Version : _____ Date : ____ / ____ / ____
 Track : _____ Track Temp: _____
 Traction : _____ Motor : _____ Rotor : _____
 Endbell : _____ Final Gear Ratio : _____
 After Run
 ESC Temp : _____ Motor Temp : _____
 Remark : _____

Quick Setup	Range	Blinky	Modified	Open stock	Off Road
Softening	Level 1-5				
Punch	Level 1-15				
PWM	2000- 32000Hz				
Boost	Off-100				
Turbo	Off-100				
Turbo Up Rate	5				
	4				
	3				
	2				
	1				
	Normal				
	-1				
	-2				
	-3				
	-4				
Turbo down Rate	5				
	4				
	3				
	2				
	1				
	Normal				
	-1				
	-2				
	-3				
	-4				
Compress	0%- 50%				
Drag Brake	Off - 30%				
Advanced Setup	Range	Blinky	Modified	Open stock	Off Road
PWM	2000- 32000Hz				
Compress	0-50%				
Boost Start	0-90%				
Boost Range	0-50%				
Turbo Delay	Off- 0.10s				
Turbo Start	40-100%				
Brake Freq	500HZ-5000HZ				
Initial Brake	0-60%				
Brake Range	0-100%				
Max Brake Force	0-100%				
Initial Setup	Range	Blinky	Modified	Open stock	Off Road
Running Mode	Forward/Brake				
	Forward/Rev				
	Forward/Brake/Rev				
	Forward/Hold/Rev				
Reverse Force	0-100%				
Batt Type	LiPoylymer				
	LI-FE				
	NiXX				
Cut off v oltage	Off				
	Low				
	Middle				
	High				
Esc Heat Protection	95				
	105				
	120				
	No Protection				
Motor Heat Protection	95				
	105				
	120				
	No Protection				
Neutral Range	2%- 15%				
Bec Voltage	6v				
	7V				
Motor direction	CCW				
	CW				